

## **MWFA**

THIS CLASS WAS CREATED TO BE FUN AND ENTERTAINING FOR THE FANS TO WATCH (TOTAL CARNAGE). IF YOU COME WITH A VEHICLE THAT IS BUILT ANYMORE THEN WHAT IS LISTED BELOW, YOU WILL NOT RUN, NO EXCEPTIONS!!!!

## THE BUILD

- Any 1980's or newer <u>two-wheel drive</u> passenger car, mini-van, mini-truck or mid-size SUV, <u>no</u> <u>half ton or bigger vehicles allowed.</u>
- 2. All vehicles must be stripped of all plastic, glass; headlights, taillights, or anything else that can falls off on the track during the show.
- 3. All vehicles must remain stock, absolutely no welding anywhere.

- 4. Bumpers must remain stock, don't alter in anyway. Factory bumper shocks must remain in factory location. You may remove the rear bumper and bumper shocks. No welding on stock bumper.
- 5. Battery can be left in stock location and spray foam may be added to secure battery. You maybe also move battery to the passenger floor or seat. Battery must be safely secured and covered.
- 6. If factory gas tank is in front of the rear axle you may leave it there. If behind the rear axle, you must move it to the rear seat compartment. Factory tank may be moved inside the vehicle but must be safely secured and leak proof. Aftermarket fuel cells may be used. If you leave the factory tank underneath vehicle in the stock location, you must secure it with two strands of #9 wire for safety.
- 7. All doors can be wired or chained in six places max per door.
- 8. Trunks, hood, tailgates, must be wired or chained in six places total. Sheet metal to metal only, nothing to the frame. *Bumpers must have two strands of #9 wire to keep it from falling off*. If trunk or tailgate is removed you lose the #9 wire for that particular area.
- 9. Rear seat bar can be added for safety. It can be welded to the <u>side posts</u>, if added metal is needed to get away from the seat, please call or text first and speak to official. This is for safety and to stop the sides of the vehicle from coming in, not to help any other part of the vehicle.
- 10. Drivers door only may have plate or door skin welded to the outside or inside. This is for driver's safety only.
- 11. <u>DOT car tires only and stock wheels</u>. All wheel weights must be removed. Only tubes and air are permitted inside of tire, No exceptions.
- 12. AWD vehicles must remove one driveshaft, if this causes the vehicle not to move or run, then the only alternative option is to run the rear wheels with no tires (rims only). You Must let official know during tech.

- 13. No spray foam at all, except to secure battery under the hood. Tech Official will make you cut it if they feel it's excessive.
- 14. All airbags and airbag assembly must be removed.

\*THESE RULES ARE CUT AND DRY. IF IT DOES NOT SAY
YOU CAN DO IT, THEN THAT MEANS YOU CANNOT DO IT.
THIS IS A QUICK AND EASY BUILD. \*

FOR QUESTIONS ON RULES AND CLARIFICATION PLEASE
TEXT CHRIS ROYER AT (740) 705-2139